

CERTIFICATE OF COMPLIANCE

Certificate Number 20190530-E199260
Report Reference E199260-20190521
Issue Date 2019-MAY-30

Issued to: BIMED TEKNİK ALETLER SAN TIC A S
BEYLIKDUZU MEVKII
SS BAKIR VE PIRINC SAN
ORKIDE CD NO 15
34524 ISTANBUL TURKEY

This certificate confirms that representative samples of OUTLET BUSHINGS AND FITTINGS
See Addendum Page

Have been investigated by UL in accordance with the Standard(s) indicated on this Certificate.

Standard(s) for Safety: UL 514B and CSA C22.2 No. 18.3-12-Conduit, Tubing, and Cable Fittings
UL 50E and CSA C22.2 No. 94.2-15-- Enclosures for Electrical Equipment, Environmental Considerations,
UL 746C-Polymeric Materials - Use in Electrical Equipment Evaluations

Additional Information: See the UL Online Certifications Directory at <https://iq.ulprospector.com> for additional information.

This *Certificate of Compliance* does not provide authorization to apply the UL Mark. Only the UL Follow-Up Services Procedure provides authorization to apply the UL Mark.

Only those products bearing the UL Mark should be considered as being UL Certified and covered under UL's Follow-Up Services.

Look for the UL Certification Mark on the product.



Bruce Mahrenholz, Director North American Certification Program

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>



CERTIFICATE OF COMPLIANCE

Certificate Number 20190530-E199260
Report Reference E199260-20190521
Issue Date 2019-MAY-30

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.

USL, CNL - Liquid-Tight Flexible Nonmetallic Conduit Connector, Series BHP, Cat. No. BHP, followed by M or N, may be followed by N, followed by -0, -1, -2, -3, -4 or -5, followed by 2, 3 or 4, may be followed by (V2).

USL, CNL - Liquid-Tight Flexible Metallic Conduit Connector, Series BHP, Cat. No. BHP, followed by -1, -2 or -3, followed by M or N, followed by BN or X, followed by C or N, may be followed by (V2), may be followed by (303), (304), (316) or (316L).



Bruce Mahrenholz, Director North American Certification Program

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>

